

PREMIUM LINE
SOLID CARBIDE
END MILLS



TABLE OF CONTENTS



SOLID CARBIDE END MILLS

Universal..... 5 - 14, 25 - 50

Steel Machining 15

Hard Materials Machining 16 - 19

Stainless Steel Machining..... 20 - 21

Non-Iron Metal & Aluminium Machining 22

Cutting Parameters for End Mills 23 - 24, 51

Machined materials

Pages colors according with group of machined materials.
All drills are universal to use.

Universal

Steel

Hard materials

Stainless steel

Aluminium and non-ferrous metals

Pictograms

Helix angle

25°

30°

35/38°

45°

50°

52°

55°

Machined materials

Universal

NE

ALU

HRC 55-60

HRC 65

Steel <1400N/mm²

INCONEL TITAN

INOX

Teeth number

2

3

4

6

8

Shaft type

HA

HB

Feed direction

For high-speed and high-performace machining

HPC

HSC

Corner radius

Point angle

140°

Drills with 4 guide margins

4 guide margins

Internal/external cooling

w/CH


w/o CH

Coating


TIALN

ALTiN

End mills code





Drills code



UNIVERSAL

Series
UNTM2

Solid carbide end mills, micro
standart, Z=2





Ø d1	Ø d2	l2	l1	Z	
0,1	3	0,3	38	2	UNTM2/2.0010HA0030
0,15	3	0,3	38	2	UNTM2/2.0015HA0030
0,2	3	0,5	38	2	UNTM2/2.0020HA0050
0,25	3	0,5	38	2	UNTM2/2.0025HA0050
0,3	3	1,0	38	2	UNTM2/2.0030HA0100
0,4	3	1,0	38	2	UNTM2/2.0040HA0100
0,5	3	1,5	38	2	UNTM2/2.0050HA0150
0,6	3	1,5	38	2	UNTM2/2.0060HA0150
0,7	3	2,0	38	2	UNTM2/2.0070HA0200
0,8	3	2,0	38	2	UNTM2/2.0080HA0200
0,9	3	2,5	38	2	UNTM2/2.0090HA0250
1,0	3	3,0	38	2	UNTM2/2.0100HA0300
1,1	3	3,0	38	2	UNTM2/2.0110HA0300
1,2	3	4,0	38	2	UNTM2/2.0120HA0400
1,3	3	4,0	38	2	UNTM2/2.0130HA0400
1,4	3	4,0	38	2	UNTM2/2.0140HA0400
1,5	3	4,0	38	2	UNTM2/2.0150HA0400
1,6	3	4,0	38	2	UNTM2/2.0160HA0400
1,7	3	4,0	38	2	UNTM2/2.0170HA0400
1,8	3	5,0	38	2	UNTM2/2.0180HA0500
1,9	3	5,0	38	2	UNTM2/2.0190HA0500
2,0	3	5,0	38	2	UNTM2/2.0200HA0500

UNIVERSAL

Series
UNTM3

Solid carbide end mills
standart, Z=3





Ø d1	Ø d2	l2	l1	Z	
1,0	3	3	38	3	UNTM3/1.0100HA0300
1,5	3	5	38	3	UNTM3/1.0150HA0500
2,0	3	7	38	3	UNTM3/1.0200HA0700
2,5	3	7	38	3	UNTM3/1.0250HA0700
3,0	3	8	38	3	UNTM3/1.0300HA0800
3,5	4	11	50	3	UNTM3/1.0350HA1100
4,0	4	11	50	3	UNTM3/1.0400HA1100
4,5	5	11	50	3	UNTM3/1.0450HA1100
5,0	5	10	50	3	UNTM3/1.0500HA1000
5,5	6	10	50	3	UNTM3/1.0550HA1000
6,0	6	10	57	3	UNTM3/1.0600HA1000
6,75	8	13	63	3	UNTM3/1.0675HA1300
7,0	8	13	63	3	UNTM3/1.0700HA1300
7,75	8	16	63	3	UNTM3/1.0775HA1600
8,0	8	16	63	3	UNTM3/1.0800HA1600
8,7	10	16	72	3	UNTM3/1.0870HA41600
9,0	10	16	72	3	UNTM3/1.0900HA1600
9,7	10	19	72	3	UNTM3/1.0970HA1900
10,0	10	22	72	3	UNTM3/1.1000HA2200
11,0	12	22	83	3	UNTM3/1.1100HA2200
11,7	12	22	83	3	UNTM3/1.1170HA2200
12,0	12	22	83	3	UNTM3/1.1200HA2200
13,7	14	22	83	3	UNTM3/1.1370HA2200
14,0	14	22	83	3	UNTM3/1.1400HA2200
15,7	16	26	83	3	UNTM3/1.1570HA2600
16,0	16	26	83	3	UNTM3/1.1600HA2600
17,7	18	26	92	3	UNTM3/1.1770HA2600
18,0	18	26	92	3	UNTM3/1.1800HA2600
19,7	20	32	104	3	UNTM3/1.1970HA3200
20,0	20	32	104	3	UNTM3/1.2000HA3200

UNIVERSAL

Series
UNDL2

Solid carbide end mills
long, Z=2





Ø d1	Ø d2	l2	l1	Z	
1,0	3	2	38	2	UNDL2/2.0100HB
1,5	3	3	38	2	UNDL2/2.0150HB
2,0	3	6	38	2	UNDL2/2.0200HB
2,5	3	6	38	2	UNDL2/2.0250HB
2,8	3	7	38	2	UNDL2/2.0280HB
3,0	3	7	38	2	UNDL2/2.0300HB
3,5	6	8	57	2	UNDL2/2.0350HB
4,0	6	8	57	2	UNDL2/2.0400HB
4,5	6	10	57	2	UNDL2/2.0450HB
4,8	6	10	57	2	UNDL2/2.0480HB
5,0	6	10	57	2	UNDL2/2.0500HB
5,5	6	10	57	2	UNDL2/2.0550HB
5,75	6	10	57	2	UNDL2/2.0575HB
6,0	6	10	57	2	UNDL2/2.0600HB
6,75	8	13	63	2	UNDL2/2.0675HB
7,0	8	16	63	2	UNDL2/2.0700HB
7,5	8	16	63	2	UNDL2/2.0750HB
7,75	8	16	63	2	UNDL2/2.0775HB
8,0	8	16	63	2	UNDL2/2.0800HB
8,7	10	16	72	2	UNDL2/2.0870HB
9,0	10	16	72	2	UNDL2/2.0900HB
9,7	10	19	72	2	UNDL2/2.0970HB
10,0	10	19	72	2	UNDL2/2.1000HB
11,7	12	22	83	2	UNDL2/2.1170HB
12,0	12	22	83	2	UNDL2/2.1200HB
13,7	14	22	83	2	UNDL2/2.1370HB
14,0	14	22	83	2	UNDL2/2.1400HB
15,7	16	26	92	2	UNDL2/2.1570HB
16,0	16	26	92	2	UNDL2/2.1600HB
18,0	18	26	92	2	UNDL2/2.1800HB
20,0	20	32	104	2	UNDL2/2.2000HB

UNIVERSAL

Series
UNDL4

Solid carbide end mills
long, Z=4





Ø d1	Ø d2	l2	l1	Z	
2,0	3	7	57	4	UNDL4/2.0200HB
3,0	6	8	57	4	UNDL4/2.0300HB
3,5	6	10	57	4	UNDL4/2.0350HB
4,0	6	11	57	4	UNDL4/2.0400HB
5,0	6	13	57	4	UNDL4/2.0500HB
6,0	6	13	57	4	UNDL4/2.0600HB
7,0	8	16	63	4	UNDL4/2.0700HB
8,0	8	19	63	4	UNDL4/2.0800HB
9,0	10	22	73	4	UNDL4/2.0900HB
10,0	10	22	72	4	UNDL4/2.1000HB
12,0	12	26	83	4	UNDL4/2.1200HB
14,0	14	26	83	4	UNDL4/2.1400HB
16,0	16	32	92	4	UNDL4/2.1600HB
18,0	18	32	92	4	UNDL4/2.1800HB
20,0	20	38	104	4	UNDL4/2.2000HB

UNIVERSAL

Series
USTS2



Solid carbide end mills, ball-nosed
short, Z=2



Ø d1	Ø d2	l2	l1	Z	
1,0	6	3	50	2	USTS2/2.0100HB0300
2,0	6	4	50	2	USTS2/2.0200HB0400
2,5	6	4	50	2	USTS2/2.0250HB0400
3,0	6	5	50	2	USTS2/2.0300HB0500
3,5	6	5	50	2	USTS2/2.0350HB0500
4,0	6	6	54	2	USTS2/2.0400HB0600
4,5	6	6	54	2	USTS2/2.0450HB0600
5,0	6	7	54	2	USTS2/2.0500HB0700
6,0	6	9	54	2	USTS2/2.0600HB0900
8,0	8	12	58	2	USTS2/2.0800HB1200
10,0	10	14	66	2	USTS2/2.1000HB1400
12,0	12	14	73	2	USTS2/2.1200HB1400
14,0	14	16	75	2	USTS2/2.1400HB1600
16,0	16	18	82	2	USTS2/2.1600HB1800
18,0	18	20	88	2	USTS2/2.1800HB2000
20,0	20	22	92	2	USTS2/2.2000HB2200

Series
USTM4

Solid carbide end mills, ball-nosed
standart, Z=4





Ø d1	Ø d2	l2	l1	Z	
3,0	3	7	38	4	USTM4/2.0300HB0700
4,0	4	14	50	4	USTM4/2.0400HB1400
5,0	6	16	50	4	USTM4/2.0500HB1600
6,0	6	19	60	4	USTM4/2.0600HB1900
8,0	8	20	60	4	USTM4/2.0800HB2000
10,0	10	21	70	4	USTM4/2.1000HB2100
12,0	12	25	75	4	USTM4/2.1200HB2500
16,0	16	32	88	4	USTM4/2.1600HB3200
20,0	20	38	104	4	USTM4/2.2000HB3800

UNIVERSAL

Series
USTM2

Solid carbide end mills, ball-nosed micro
standart, Z=2



Ø d1	Ø d2	l2	l1	Z	
0,2	3	0,5	38	2	USTM2/2.0020HA0050
0,25	3	0,5	38	2	USTM2/2.0025HA0050
0,3	3	1,0	38	2	USTM2/2.0030HA0100
0,4	3	1,0	38	2	USTM2/2.0040HA0100
0,5	3	1,5	38	2	USTM2/2.0050HA0150
0,6	3	1,5	38	2	USTM2/2.0060HA0150
0,7	3	2,0	38	2	USTM2/2.0070HA0200
0,8	3	2,0	38	2	USTM2/2.0080HA0200
0,9	3	2,5	38	2	USTM2/2.0090HA0250
1,0	3	3,0	38	2	USTM2/2.0100HA0300
1,1	3	3,0	38	2	USTM2/2.0110HA0300
1,2	3	4,0	38	2	USTM2/2.0120HA0300
1,4	3	4,0	38	2	USTM2/2.0140HA0400
1,5	3	4,0	38	2	USTM2/2.0150HA0400
1,6	3	5,0	38	2	USTM2/2.0160HA0500
1,8	3	5,0	38	2	USTM2/2.0180HA0500
2,0	3	5,0	38	2	USTM2/2.0200HA0500

UNIVERSAL

Series
UPTM4

Solid carbide end mills for rough machining
standart, Z=4





Ø d1	Ø d2	l2	l1	Z	
3,0	6	6	57	4	UPTM4.0300HB0600
4,0	6	8	57	4	UPTM4.0400HB0800
5,0	6	10	57	4	UPTM4.0500HB1000
6,0	6	13	57	4	UPTM4.0600HB1300
8,0	8	16	63	4	UPTM4.0800HB1600
10,0	10	22	72	4	UPTM4.1000HB2200
12,0	12	26	83	4	UPTM4.1200HB2600
14,0	14	26	83	4	UPTM4.1400HB2600
16,0	16	32	92	4	UPTM4.1600HB3200
20,0	20	38	104	4	UPTM4.2000HB3800
25,0	25	45	121	4	UPTM4.2500HB4500

UNIVERSAL

Series
UFTM4

Solid carbide end mills, profile
standart, Z=4




Ø d1	Ø d2	l1	R	Z	
5,6	6	58	0,2	4	UF02TM4.0560
5,4	6	58	0,3	4	UF03TM4.0540
5,2	6	58	0,4	4	UF04TM4.0520
7,0	8	70	0,5	4	UF05TM4.0700
6,0	8	70	1,0	4	UF10TM4.0600
7,0	10	75	1,5	4	UF15TM4.0700
6,0	10	75	2,0	4	UF20TM4.0600
7,0	12	75	2,5	4	UF25TM4.0700
6,0	12	75	3,0	4	UF30TM4.0600
9,0	16	80	3,5	4	UF35TM4.0900
8,0	16	80	4,0	4	UF40TM4.0800
7,0	16	80	4,5	4	UF45TM4.7800
10,0	20	80	5,0	4	UF50TM4.1000
8,0	20	80	6,0	4	UF60TM4.0800
9,0	25	100	8,0	4	UF80TM4.0900
5,0	25	100	10,0	4	UF100TM4.0500

UNIVERSAL

Series
UK90DL3/4

Solid carbide end mills for chamfering
Z=3/4





Ø d1	Ø d2	l1	Z	
1,0	3	38	3	UK90DL3.0100HB
2,0	3	38	3	UK90DL3.0200HB
3,0	3	38	4	UK90DL4.0300HB
4,0	4	54	4	UK90DL4.0400HB
6,0	6	57	4	UK90DL4.0600HB
8,0	8	63	4	UK90DL4.0800HB
10,0	10	72	4	UK90DL4.1000HB
12,0	12	83	4	UK90DL4.1200HB
16,0	16	92	4	UK90DL4.1600HB
20,0	20	104	4	UK90DL4.2000HB

UNIVERSAL

Series
UNDL6/8

Solid carbide end mills
long, Z=6/8




Ø d1	Ø d2	l2	l1	Ø d3	l3	Z	
3,0	6	8	57	2,7	11	6	UNDL6.0300HB
4,0	6	11	57	3,7	16	6	UNDL6.0400HB
5,0	6	13	57	4,6	18	6	UNDL6.0500HB
6,0	6	13	57	5,5	18	6	UNDL6.0600HB
8,0	8	19	63	7,5	24	6	UNDL6.0800HB
10,0	10	22	72	9,5	32	6	UNDL6.1000HB
12,0	12	26	83	11,5	36	6	UNDL6.1200HB
14,0	14	26	83	13,5	36	6	UNDL6.1400HB
16,0	16	32	92	15,5	42	6	UNDL6.1600HB
18,0	18	32	92	17,5	42	8	UNDL8.1800HB
20,0	20	38	104	19,5	48	8	UNDL8.2000HB
25,0	25	45	121	24,5	65	8	UNDL8.2500HB

STEEL MACHINING

Series
PRTM3/4

Solid carbide end mills, corner radius
standart, Z=3/4



Universal

HRC 55-60



HPC

Ø d1	Ø d2	l2	l1	R	Ø d3	l3	Z	
3,0	6	8	57	0,2	2,9	18	3	PR02TM3/1.0300HA0800
3,0	6	8	57	0,5	2,9	18	3	PR05TM3/1.0300HA0800
4,0	6	11	57	0,3	3,8	21	4	PR03TM4/2.0400HA1100
4,0	6	11	57	0,5	3,8	21	4	PR05TM4/2.0400HA1100
4,0	6	11	57	1,0	3,8	21	4	PR10TM4/2.0400HA1100
5,0	6	13	57	0,3	4,8	21	4	PR03TM4/2.0500HA1300
5,0	6	13	57	0,5	4,8	21	4	PR05TM4/2.0500HA1300
5,0	6	13	57	1,0	4,8	21	4	PR10TM4/2.0500HA1300
6,0	6	13	57	0,3	5,8	21	4	PR03TM4/2.0600HA1300
6,0	6	13	57	0,5	5,8	21	4	PR05TM4/2.0600HA1300
6,0	6	13	57	1,0	5,8	21	4	PR10TM4/2.0600HA1300
6,0	6	13	57	1,5	5,8	21	4	PR15TM4/2.0600HA1300
6,0	6	13	57	2,0	5,8	21	4	PR20TM4/2.0600HA1300
8,0	8	19	63	0,5	7,8	27	4	PR05TM4/2.0800HA1900
8,0	8	19	63	1,0	7,8	27	4	PR10TM4/2.0800HA1900
8,0	8	19	63	1,5	7,8	27	4	PR15TM4/2.0800HA1900
8,0	8	19	63	2,0	7,8	27	4	PR20TM4/2.0800HA1900
10,0	10	22	72	0,5	9,8	32	4	PR05TM4/2.1000HA2200
10,0	10	22	72	1,0	9,8	32	4	PR10TM4/2.1000HA2200
10,0	10	22	72	1,5	9,8	32	4	PR15TM4/2.1000HA2200
10,0	10	22	72	2,0	9,8	32	4	PR20TM4/2.1000HA2200
12,0	12	26	83	0,5	11,8	38	4	PR05TM4/2.1200HA2600
12,0	12	26	83	1,0	11,8	38	4	PR10TM4/2.1200HA2600
12,0	12	26	83	1,5	11,8	38	4	PR15TM4/2.1200HA2600
12,0	12	26	83	2,0	11,8	38	4	PR20TM4/2.1200HA2600
16,0	16	32	92	0,5	15,8	44	4	PR05TM4/2.1600HA3200
16,0	16	32	92	1,0	15,8	44	4	PR10TM4/2.1600HA3200
16,0	16	32	92	1,5	15,8	44	4	PR15TM4/2.1600HA3200
16,0	16	32	92	2,0	15,8	44	4	PR20TM4/2.1600HA3200
16,0	16	32	150	1,0	15,8	44	4	PR10XTM4/2.1600HA3200
20,0	20	38	92	0,5	19,8	54	4	PR05TM4/2.2000HA3800
20,0	20	38	92	1,0	19,8	54	4	PR10TM4/2.2000HA3800
20,0	20	38	92	1,5	19,8	54	4	PR15TM4/2.2000HA3800
20,0	20	38	92	2,0	19,8	54	4	PR20TM4/2.2000HA3800
20,0	20	38	150	1,0	19,8	54	4	PR10XTM4/2.2000HA3800
25,0	25	38	160	2,0	19,8	54	4	PR20TM4/2.2500HA3800

HARD MATERIALS MACHINING

Series
HNTS6/8

Solid carbide end mills
short, Z=6/8





Ø d1	Ø d2	l2	l1	Z	
4,0	6	10	54	6	HNTS6.0400HA1000
5,0	6	10	54	6	HNTS6.0500HA1000
6,0	6	10	54	6	HNTS6.0600HA1000
7,0	8	12	58	6	HNTS6.0700HA1200
8,0	8	12	58	6	HNTS6.0800HA1200
9,0	10	14	66	6	HNTS6.0900HA1400
10,0	10	14	66	6	HNTS6.1000HA1400
12,0	12	16	73	6	HNTS6.1200HA1600
14,0	14	20	82	8	HNTS8.1400HA2000
16,0	16	20	82	8	HNTS8.1600HA2000
18,0	18	25	92	8	HNTS8.1800HA2500
20,0	20	25	92	8	HNTS8.2000HA2500

HARD MATERIALS MACHINING

Series
HNTM6/8



Solid carbide end mills
standart, Z=6/8



Ø d1	Ø d2	l2	l1	Z	
3,0	6	8	57	6	HNTM6.0300HA0800
4,0	6	11	57	6	HNTM6.0400HA1100
5,0	6	13	57	6	HNTM6.0500HA1300
6,0	6	13	57	6	HNTM6.0600HA1300
8,0	8	19	63	6	HNTM6.0800HA4900
10,0	10	22	72	6	HNTM6.1000HA2200
12,0	12	26	83	6	HNTM6.1200HA2600
14,0	14	26	83	8	HNTM8.1400HA2600
16,0	16	32	92	8	HNTM8.1600HA3200
18,0	18	32	92	8	HNTM8.1800HA3200
20,0	20	38	104	8	HNTM8.2000HA3800

Series
HRTL6/8

Solid carbide end mills, corner radius
long, Z=6/8





Ø d1	Ø d2	l2	l1	R	Z	
6,0	6	18	62	0,5	6	HR05TL6.0600HA1800
8,0	8	24	68	0,5	6	HR05TL6.0800HA2400
8,0	8	24	68	1,0	6	HR10TL6.0800HA2400
10,0	10	30	80	0,5	6	HR05TL6.1000HA3000
10,0	10	30	80	1,0	6	HR15TL6.1000HA3000
12,0	12	36	93	0,5	6	HR05TL6.1200HA3600
12,0	12	36	93	1,0	6	HR10TL6.1200HA3600
12,0	12	36	93	1,5	6	HR15TL6.1200HA3600
12,0	12	36	93	2,0	6	HR20TL6.1200HA3600
16,0	16	48	108	0,5	8	HR05TL8.1600HA4800
16,0	16	48	108	1,0	8	HR10TL8.1600HA4800
16,0	16	48	108	1,5	8	HR15TL8.1600HA4800
16,0	16	48	108	2,0	8	HR20TL8.1600HA4800
20,0	20	60	126	2,0	8	HR20TL8.2000HA6000

HARD MATERIALS MACHINING

Series
HRTM6/8

Solid carbide end mills, corner radius
standart, Z=6/8




Ø d1	Ø d2	l2	l1	R	Z	
6,0	6	13	57	0,5	6	HR05TM6.0600HA1300
6,0	6	13	57	1,0	6	HR10TM6.0600HA1300
8,0	8	19	63	0,5	6	HR05TM6.0800HA1900
8,0	8	19	63	1,0	6	HR10TM6.0800HA1900
10,0	10	22	72	0,5	6	HR05TM6.1000HA2200
10,0	10	22	72	1,0	6	HR10TM6.1000HA2200
12,0	12	26	83	0,5	6	HR05TM6.1200HA2600
12,0	12	26	83	1,0	6	HR10TM6.1200HA2600
12,0	12	26	83	1,5	6	HR15TM6.1200HA2600
12,0	12	26	83	2,0	6	HR20TM6.1200HA2600
12,0	12	26	83	2,5	6	HR25TM6.1200HA2600
16,0	16	32	92	0,5	8	HR05TM8.1600HA3200
16,0	16	32	92	1,0	8	HR10TM8.1600HA3200
16,0	16	32	92	1,5	8	HR15TM8.1600HA3200
16,0	16	32	92	2,0	8	HR20TM8.1600HA3200
16,0	16	32	92	2,5	8	HR25TM8.1600HA3200
16,0	16	32	92	3,0	8	HR30TM8.1600HA3200
20,0	20	38	104	2,5	8	HR20TM8.2000HA3800

HARD MATERIALS MACHINING

Series
HSTL2

Solid carbide end mills, ball-nosed
long, Z=2



HSC

HRC 65

HA

TIALN

Ø d1	Ø d2	l2	l1	Z	
1,0	3	1,5	50	2	HSTL2/2.0100HA
1,5	3	5,5	50	2	HSTL2/2.0150HA
2,0	3	3,0	50	2	HSTL2/2.0200HA
2,5	3	4,0	50	2	HSTL2/2.0250HA
3,0	3	6,0	75	2	HSTL2/2.0300HA
4,0	4	8,0	75	2	HSTL2/2.0400HA
5,0	6	10,0	75	2	HSTL2/2.0500HA
6,0	6	12,0	100	2	HSTL2/2.0600HA
8,0	8	14,0	100	2	HSTL2/2.0800HA
10,0	10	18,0	100	2	HSTL2/2.1000HA
12,0	12	22,0	150	2	HSTL2/2.1200HA
14,0	14	26,0	150	2	HSTL2/2.1400HA
16,0	16	30,0	150	2	HSTL2/2.1600HA
18,0	18	34,0	150	2	HSTL2/2.1800HA
20,0	20	38,0	150	2	HSTL2/2.2000HA

Series
HSTS2

Solid carbide end mills, ball-nosed
short, Z=2



HSC

HRC 65

HA



TIALN

Ø d1	Ø d2	l2	l1	Z	
3,0	3	6	50	2	HSTS2/2.0300HA0600
4,0	4	8	54	2	HSTS2/2.0400HA0800
5,0	6	10	54	2	HSTS2/2.0500HA1000
6,0	6	12	54	2	HSTS2/2.0600HA1200
8,0	8	14	58	2	HSTS2/2.0800HA1400
10,0	10	18	66	2	HSTS2/2.1000HA1800
12,0	12	22	73	2	HSTS2/2.1200HA2200
14,0	14	26	75	2	HSTS2/2.1400HA2600
16,0	16	30	82	2	HSTS2/2.1600HA3000
18,0	18	34	84	2	HSTS2/2.1800HA3400
20,0	20	38	92	2	HSTS2/2.2000HA3800

STAINLESS STEEL MACHINING

Series
MCTS4

Solid carbide end mills
short, Z=4





Ø d1	Ø d2	l2	l1	φ packa	Z	
3,0	6	6	54	0,1	4	MC01TS4/2.0300HB0600
4,0	6	8	54	0,13	4	MC013TS4/2.0400HB0800
5,0	6	9	54	0,18	4	MC018TS4/2.0500HB0900
6,0	6	10	54	0,2	4	MC02TS4/2.0600HB1000
7,0	8	12	58	0,2	4	MC02TS4/2.0700HB1200
8,0	8	12	58	0,2	4	MC02TS4/2.0800HB1200
9,0	10	14	66	0,3	4	MC03TS4/2.0900HB1400
10,0	10	14	66	0,3	4	MC03TS4/2.1000HB1400
11,0	12	16	73	0,3	4	MC03TS4/2.1100HB1600
12,0	12	16	73	0,3	4	MC03TS4/2.1200HB1600
13,0	14	18	75	0,3	4	MC03TS4/2.1300HB1800
14,0	14	18	75	0,3	4	MC03TS4/2.1400HB1800
16,0	16	22	82	0,4	4	MC04TS4/2.1600HB2200
18,0	18	24	84	0,4	4	MC04TS4/2.1800HB2400
20,0	20	26	92	0,5	4	MC05TS4/2.2000HB2600
25,0	25	32	92	0,5	4	MC05TS4/2.2500HB3200

STAINLESS STEEL MACHINING

Series
MCTM4



Solid carbide end mills
standart, Z=4



Ø d1	Ø d2	l2	l1	Ø d3	l3	φ packa	Z	
3,0	6	8	57	2,8	18	0,13	4	MC013TM4/2.0300HB0800
4,0	6	11	57	3,6	21	0,13	4	MC013TM4/2.0400HB1100
5,0	6	13	57	4,6	21	0,18	4	MC018TM4/2.0500HB1300
6,0	6	13	57	5,5	21	0,2	4	MC02TM4/2.0600HB1300
7,0	8	19	63	6,5	27	0,2	4	MC02TM4/2.0700HB1900
8,0	8	19	63	7,5	27	0,2	4	MC02TM4/2.0800HB1900
9,0	10	22	72	8,5	32	0,3	4	MC03TM4/2.0900HB2200
10,0	10	22	72	9,5	32	0,3	4	MC03TM4/2.1000HB2200
11,0	12	26	83	10,5	38	0,3	4	MC03TM4/2.1100HB2600
12,0	12	26	83	11,5	38	0,3	4	MC03TM4/2.1200HB2600
14,0	14	26	83	13,5	42	0,3	4	MC03TM4/2.1400HB2600
16,0	16	32	92	15,5	44	0,4	4	MC04TM4/2.1600HB3200
18,0	18	32	92	17,5	50	0,4	4	MC04TM4/2.1800HB3200
20,0	20	38	104	19,5	54	0,5	4	MC05TM4/2.2000HB3800
25,0	25	42	104	24	65	0,5	4	MC05TM4/2.2500HB4200

Series
MPTL4

Solid carbide end mills
long, Z=4





Ø d1	Ø d2	l2	l1	Ø d3	l3	φ packa	Z	
6,0	6	22	80	5,7	40	0,4	4	MPTL4.0600HB2200
8,0	8	27	100	7,4	50	0,4	4	MPTL4.0800HB2700
10,0	10	32	100	9,2	60	0,4	4	MPTL4.1000HB3200
12,0	12	42	120	11,0	60	0,4	4	MPTL4.1200HB4200
16,0	16	52	150	15,0	100	0,4	4	MPTL4.1600HB5200
20,0	20	62	150	19,0	100	0,4	4	MPTL4.2000HB6200
25,0	25	82	150	24,0	100	0,5	4	MPTL4.2500HB8200

NON-IRON METAL & ALUMINIUM MACHINING

Series
NNTL3



Solid carbide end mills
long, Z=3



Ø d1	Ø d2	l2	l1	Z	
6,0	6	16	60	3	NNTL3/1.0600HA1600
8,0	8	25	78	3	NNTL3/1.0800HA2500
10,0	10	28	78	3	NNTL3/1.1000HA2800
12,0	12	32	89	3	NNTL3/1.1200HA3200
14,0	14	32	89	3	NNTL3/1.1400HA3200
16,0	16	36	104	3	NNTL3/1.1600HA3600
20,0	20	45	111	3	NNTL3/1.2000HA4500
25,0	25	50	126	3	NNTL3/1.2500HA5000

Series
NNDL2

Solid carbide end mills
long, Z=2



Ø d1	Ø d2	l2	l1	Z	
3,0	6	8	57	2	NNDL2/2.0300HB
4,0	6	11	57	2	NNDL2/2.0400HB
5,0	6	13	57	2	NNDL2/2.0500HB
6,0	6	13	57	2	NNDL2/2.0600HB
8,0	8	19	63	2	NNDL2/2.0800HB
10,0	10	22	72	2	NNDL2/2.1000HB
12,0	12	26	83	2	NNDL2/2.1200HB
14,0	14	26	83	2	NNDL2/2.1400HB
16,0	16	32	92	2	NNDL2/2.1600HB
18,0	18	32	92	2	NNDL2/2.1800HB
20,0	20	38	104	2	NNDL2/2.2000HB

Cutting parameters for UNDL2, NNTL3, NNDL2, UNDL4, UNTM3 series

	(Nm/mm ²)	Vc (m/min)	ø2 fz	ø3 fz	ø4 fz	ø5 fz	ø6 fz	ø8 fz	ø10 fz	ø12 fz	ø14 fz	ø16 fz	ø18-20 fz
general structural steels	< 500	120	0,012	0,012	0,025	0,030	0,037	0,051	0,068	0,090	0,100	0,113	0,135
general structural steels	>700	105	0,012	0,012	0,025	0,030	0,037	0,051	0,068	0,090	0,100	0,113	0,135
free cutting steels	< 850	95	0,012	0,012	0,025	0,030	0,037	0,051	0,068	0,090	0,100	0,113	0,135
free cutting steels	850 - 1000	90	0,012	0,012	0,025	0,030	0,037	0,051	0,068	0,090	0,100	0,113	0,135
free cutting steels	1400	80	0,008	0,012	0,018	0,018	0,028	0,040	0,055	0,070	0,080	0,090	0,110
alloyed case-hardened steels	1000	80	0,008	0,008	0,015	0,015	0,018	0,030	0,035	0,040	0,040	0,060	0,080
nitriding steels	1000	80	0,008	0,008	0,015	0,015	0,018	0,030	0,035	0,040	0,040	0,060	0,080
alloyed heat-treated steels	850	100	0,010	0,010	0,020	0,020	0,030	0,040	0,050	0,060	0,060	0,080	0,100
tool steels		70	0,008	0,012	0,018	0,018	0,028	0,040	0,055	0,070	0,080	0,090	0,110
cast iron	< 180 HB	120	0,008	0,008	0,015	0,020	0,020	0,030	0,040	0,045	0,045	0,060	0,080
nodular graphite and malleable iron		60	0,011	0,023	0,027	0,030	0,033	0,045	0,056	0,068	0,075	0,090	0,115
cast iron with nodular graphite		90	0,011	0,023	0,027	0,030	0,033	0,045	0,056	0,068	0,075	0,090	0,115
AL- and AL-alloys (under 12% Si)		200	0,008	0,008	0,015	0,015	0,025	0,030	0,040	0,050	0,050	0,065	0,085
AL- and AL-alloys (under 12 % Si)		200	0,012	0,012	0,025	0,030	0,037	0,051	0,068	0,090	0,100	0,113	0,135
Brass, copper, bronze, red brass		80	0,012	0,012	0,025	0,030	0,037	0,051	0,068	0,090	0,100	0,113	0,135
Duroplastics and thermoplastics		40											
Titanium and titaniul alloys		60	0,008	0,012	0,013	0,016	0,019	0,028	0,036	0,051	0,060	0,068	0,084

Cutting parameters for PR02TM3 series

	(Nm/mm ²)	Vc (m/min)	ø4 fz	ø5 fz	ø6 fz	ø8 fz	ø10 fz	ø12 fz	ø16 fz	ø20 fz
General structural steels	<500	250	0,045	0,045	0,055	0,07	0,08	0,10	0,12	0,12
Free cutting steels	<850	240	0,040	0,040	0,055	0,06	0,07	0,08	0,10	0,10
Non-alloyed heat-treated steels	700-850	200	0,040	0,040	0,050	0,06	0,07	0,08	0,10	0,10
Alloyed heat-treated steels	850-1000	180	0,040	0,040	0,050	0,06	0,07	0,08	0,10	0,10
Rust-proof steels, austenitic	<700	120	0,025	0,025	0,035	0,04	0,04	0,05	0,07	0,07
Cast iron	<180 HB	200	0,045	0,045	0,055	0,07	0,08	0,01	0,12	0,12
Titanium and titanium alloys	<850	160	0,040	0,040	0,040	0,06	0,07	0,08	0,10	0,10
Copper low-alloyed	<400	280	0,045	0,045	0,055	0,07	0,08	0,10	0,12	0,12

Cutting parameters for MC013TM4, MC01TS4 series

	(Nm/mm ²)	Vc (m/min)	ø6 fz	ø8 fz	ø10 fz	ø12 fz	ø16 fz	ø20 fz
general structural steels	<500	300	0,030	0,038	0,049	0,060	0,071	0,086
general structural steels	500-850	280	0,030	0,038	0,045	0,056	0,068	0,079
free cutting steels	<850	230	0,030	0,038	0,045	0,056	0,068	0,079
free cutting steels	850-1000	150	0,026	0,038	0,041	0,049	0,060	0,075
non-alloyed heat-treated steels	<700	230	0,019	0,026	0,034	0,041	0,049	0,060
non-alloyed heat-treated steels	700-850	230	0,030	0,040	0,045	0,060	0,075	0,090
non-alloyed heat-treated steels	850-1000	230	0,025	0,035	0,045	0,05	0,065	0,086
alloyed heat-treated steels	850-1000	230	0,025	0,035	0,045	0,05	0,065	0,086
alloyed heat-treated steels	1000-1200	190	0,02	0,03	0,04	0,05	0,06	0,075
Non-alloyed steels	850-1000	250	0,03	0,04	0,05	0,065	0,08	0,1
Tool steels	<850	240	0,025	0,035	0,045	0,05	0,065	0,08
Tool steels	850-1100	230	0,025	0,035	0,045	0,05	0,065	0,08
Tool steels	1100-1400	220	0,02	0,03	0,04	0,045	0,6	0,075
Rust-proof steels, sulfated	<700	150	0,025	0,035	0,045	0,055	0,065	0,08
Rust-proof steels, austenitic	<700	120	0,02	0,03	0,04	0,05	0,06	0,075
Rust-proof steels, austenitic	>850	110	0,025	0,035	0,045	0,055	0,065	0,08
Rust-proof steels, martensitic	<1100	110	0,02	0,03	0,04	0,05	0,06	0,075
Cast iron	<180HB	200	0,04	0,05	0,065	0,08	0,095	0,115
Cast iron	>180HB	150	0,035	0,045	0,06	0,075	0,09	0,11
Cast iron (GGG, GT)	>180HB	150	0,04	0,05	0,065	0,08	0,095	0,115
Cast iron (GGG, GT)	>260HB	120	0,035	0,045	0,06	0,075	0,09	0,11
Titanium, titanium alloys	>850	70	0,02	0,03	0,04	0,05	0,06	0,075
Titanium, titanium alloys	850-1200	60	0,025	0,03	0,04	0,045	0,055	0,065

Cutting parameters for UNDL6, HNTS6, HR05TL6, HNTM8, HR05TM6 series

	(Nm/mm ²)	Vc (m/min)	ø2 fz	ø4 fz	ø6 fz	ø8 fz	ø10 fz	ø12 fz	ø16 fz	ø20 fz
alloyed steel	<1200 до 35 HRC	130	0,018	0,040	0,060	0,080	0,100	0,110	0,140	0,180
low tempered steel	<1450 до 45 HRC	120	0,010	0,025	0,040	0,055	0,065	0,070	0,800	0,100
tempered steel	45-55 HRC	100	0,010	0,025	0,035	0,045	0,055	0,060	0,070	0,090
tempered steel	55-65 HRC	80	0,010	0,020	0,030	0,040	0,050	0,060	0,070	0,080
tempered steel	65-70 HRC	60	0,008	0,020	0,030	0,040	0,045	0,050	0,060	0,070

Cutting parameters for UPTM4, MPTL4 series


	(Nm/mm ²)	Vc (m/min)	ø6 fz	ø8 fz	ø10 fz	ø12 fz	ø14 fz	ø16 fz	ø20 fz
alloyed steel	400-800	170	0,010	0,020	0,025	0,030	0,040	0,050	0,065
rust-proof steel, austenitic	>1200	150	0,020	0,030	0,040	0,050	0,080	0,100	0,120
rust-proof steel, martensitic	>1200	160	0,030	0,040	0,050	0,060	0,100	0,120	0,150
titanium	>1100	100	0,050	0,080	0,100	0,120	0,140	0,160	0,200
titanium	>1500	80	0,050	0,080	0,100	0,120	0,140	0,160	0,200
nickel	>1600	70	0,040	0,060	0,070	0,100	0,120	0,150	0,200
Hardox, Inconel, Waspaloy	>1300	50	0,040	0,060	0,070	0,100	0,120	0,150	0,200

Cutting parameters for UNTM2, USTM2 series

	(N/mm ²)	Vc (m/min)	ø0,2-0,4	ø0,5	ø0,6	ø0,8	ø1,0	ø1,5	ø2,0	ø3,0	ø4,0	ø5,0	ø6,0
general structural steels	< 50	190	0,004	0,004	0,006	0,006	0,009	0,009	0,018	0,025	0,035	0,061	0,061
general structural steels	> 500 - 850	170	0,004	0,004	0,006	0,006	0,009	0,009	0,018	0,025	0,035	0,061	0,061
free cutting steels	< 850	170	0,004	0,004	0,006	0,006	0,009	0,009	0,018	0,025	0,035	0,061	0,061
free cutting steels	850 - 1000	140	0,003	0,003	0,004	0,004	0,006	0,006	0,013	0,018	0,025	0,041	0,041
non-alloyed heat-treated steels	< 700	150	0,003	0,003	0,004	0,004	0,006	0,006	0,011	0,015	0,023	0,034	0,034
non-alloyed heat-treated steels	700 - 850	130	0,003	0,003	0,004	0,004	0,006	0,006	0,013	0,018	0,025	0,041	0,041
non-alloyed heat-treated steels	850 - 1000	110	0,003	0,003	0,004	0,004	0,006	0,006	0,013	0,018	0,025	0,041	0,041
alloyed heat-treated steels	850 - 1000	95	0,004	0,004	0,006	0,006	0,009	0,009	0,018	0,025	0,035	0,061	0,030
alloyed heat-treated steels	1000 - 1200	80	0,003	0,003	0,004	0,004	0,006	0,006	0,011	0,015	0,023	0,034	0,030
non-alloyed case-hardened steels	< 750	130	0,004	0,004	0,005	0,006	0,012	0,015	0,020	0,030	0,050	0,080	0,030
alloyed case-hardened steels	850 - 1000	110	0,004	0,004	0,005	0,006	0,012	0,015	0,020	0,030	0,050	0,080	0,035
alloyed case-hardened steels	1000 - 1200	75	0,003	0,003	0,004	0,005	0,010	0,012	0,018	0,025	0,035	0,070	0,035
nitriding steels	> 850 - 1000	110	0,004	0,004	0,005	0,006	0,012	0,015	0,020	0,030	0,050	0,080	0,035
nitriding steels	1000 - 1200	75	0,004	0,004	0,005	0,006	0,012	0,015	0,020	0,030	0,050	0,080	0,035
tool steels	< 850	110	0,004	0,004	0,005	0,006	0,012	0,015	0,020	0,030	0,050	0,080	0,035
tool steels	850 - 1000	85	0,004	0,004	0,005	0,006	0,012	0,015	0,020	0,030	0,050	0,080	0,035
rust-proof steels, sulfated	< 850	110	0,003	0,003	0,004	0,005	0,010	0,012	0,018	0,025	0,035	0,070	0,800
rust-proof steels, austenitic	< 850	90	0,004	0,004	0,005	0,006	0,012	0,015	0,020	0,030	0,050	0,080	0,100
tempered steel	45 - 55 HRC	100	0,004	0,004	0,006	0,006	0,009	0,010	0,025	0,035	0,035	0,061	0,061
tempered steel	55 - 65 HRC	80	0,003	0,003	0,005	0,005	0,007	0,008	0,015	0,020	0,020	0,030	0,004
tempered steel	65 - 70 HRC	60	0,002	0,0025	0,004	0,004	0,006	0,007	0,012	0,012	0,017	0,022	0,030

UNIVERSAL

Solid carbide drills 3xD



Ø d1	Ø d2	l2	l1	Max. depth of drilling
3,00	6	20	62	14
3,10	6	20	62	14
3,20	6	20	62	14
3,30	6	20	62	14
3,40	6	20	62	14
3,50	6	20	62	14
3,60	6	20	62	14
3,70	6	20	62	14
3,80	6	24	66	17
3,90	6	24	66	17
4,00	6	24	66	17
4,10	6	24	66	17
4,20	6	24	66	17
4,30	6	24	66	17
4,40	6	24	66	17
4,50	6	24	66	17
4,60	6	24	66	17
4,70	6	24	66	17
4,80	6	28	66	20
4,90	6	28	66	20
5,00	6	28	66	20
5,10	6	28	66	20
5,20	6	28	66	20
5,30	6	28	66	20
5,40	6	28	66	20
5,50	6	28	66	20
5,60	6	28	66	20
5,70	6	28	66	20
5,80	6	28	66	20
5,90	6	28	66	20
6,00	6	28	66	20
6,10	8	34	79	24
6,20	8	34	79	24
6,30	8	34	79	24
6,40	8	34	79	24

Series I03

I03.0300U
I03.0310U
I03.0320U
I03.0330U
I03.0340U
I03.0350U
I03.0360U
I03.0370U
I03.0380U
I03.0390U
I03.0400U
I03.0410U
I03.0420U
I03.0430U
I03.0440U
I03.0450U
I03.0460U
I03.0470U
I03.0480U
I03.0490U
I03.0500U
I03.0510U
I03.0520U
I03.0530U
I03.0540U
I03.0550U
I03.0560U
I03.0570U
I03.0580U
I03.0590U
I03.0600U
I03.0610U
I03.0620U
I03.0630U
I03.0640U

Universal

TIALN

Series E03


E03.0300U
E03.0310U
E03.0320U
E03.0330U
E03.0340U
E03.0350U
E03.0360U
E03.0370U
E03.0380U
E03.0390U
E03.0400U
E03.0410U
E03.0420U
E03.0430U
E03.0440U
E03.0450U
E03.0460U
E03.0470U
E03.0480U
E03.0490U
E03.0500U
E03.0510U
E03.0520U
E03.0530U
E03.0540U
E03.0550U
E03.0560U
E03.0570U
E03.0580U
E03.0590U
E03.0600U
E03.0610U
E03.0620U
E03.0630U
E03.0640U

Universal

TIALN

UNIVERSAL

Solid carbide drills 3xD



Ø d1	Ø d2	l2	l1	Max. depth of drilling
6,50	8	34	79	24
6,60	8	34	79	24
6,70	8	34	79	24
6,80	8	34	79	24
6,90	8	34	79	24
7,00	8	34	79	24
7,10	8	41	79	29
7,20	8	41	79	29
7,30	8	41	79	29
7,40	8	41	79	29
7,50	8	41	79	29
7,60	8	41	79	29
7,70	8	41	79	29
7,80	8	41	79	29
7,90	8	41	79	29
8,00	8	41	79	29
8,10	10	47	89	35
8,20	10	47	89	35
8,30	10	47	89	35
8,40	10	47	89	35
8,50	10	47	89	35
8,60	10	47	89	35
8,70	10	47	89	35
8,80	10	47	89	35
8,90	10	47	89	35
9,00	10	47	89	35
9,10	10	47	89	35
9,20	10	47	89	35
9,30	10	47	89	35
9,40	10	47	89	35
9,50	10	47	89	35
9,60	10	47	89	35
9,70	10	47	89	35
9,80	10	47	89	35

Series I03

I03.0650U
I03.0660U
I03.0670U
I03.0680U
I03.0690U
I03.0700U
I03.0710U
I03.0720U
I03.0730U
I03.0740U
I03.0750U
I03.0760U
I03.0770U
I03.0780U
I03.0790U
I03.0800U
I03.0810U
I03.0820U
I03.0830U
I03.0840U
I03.0850U
I03.0860U
I03.0870U
I03.0880U
I03.0890U
I03.0900U
I03.0910U
I03.0920U
I03.0930U
I03.0940U
I03.0950U
I03.0960U
I03.0970U
I03.0980U

Universal

TIALN

Series E03


E03.0650U
E03.0660U
E03.0670U
E03.0680U
E03.0690U
E03.0700U
E03.0710U
E03.0720U
E03.0730U
E03.0740U
E03.0750U
E03.0760U
E03.0770U
E03.0780U
E03.0790U
E03.0800U
E03.0810U
E03.0820U
E03.0830U
E03.0840U
E03.0850U
E03.0860U
E03.0870U
E03.0880U
E03.0890U
E03.0900U
E03.0910U
E03.0920U
E03.0930U
E03.0940U
E03.0950U
E03.0960U
E03.0970U
E03.0980U

Universal

TIALN

UNIVERSAL

Solid carbide drills 3xD



Series I03

Ø d1	Ø d2	l2	l1	Max. depth of drilling
9,90	10	47	89	35
10,00	10	47	89	35
10,10	12	55	102	40
10,20	12	55	102	40
10,30	12	55	102	40
10,40	12	55	102	40
10,50	12	55	102	40
10,60	12	55	102	40
10,70	12	55	102	40
10,80	12	55	102	40
10,90	12	55	102	40
11,00	12	55	102	40
11,10	12	55	102	40
11,20	12	55	102	40
11,30	12	55	102	40
11,40	12	55	102	40
11,50	12	55	102	40
11,60	12	55	102	40
11,70	12	55	102	40
11,80	12	55	102	40
11,90	12	55	102	40
12,00	12	55	102	40
12,30	14	60	107	43
12,50	14	60	107	43
12,80	14	60	107	43
13,00	14	60	107	43
13,50	14	60	107	43
13,80	14	60	107	43
14,00	14	60	107	43
14,50	16	65	115	45
14,80	16	65	115	45
15,00	16	65	115	45
15,50	16	65	115	45
15,80	16	65	115	45
16,00	16	65	115	45

I03.0990U
I03.1000U
I03.1010U
I03.1020U
I03.1030U
I03.1040U
I03.1050U
I03.1060U
I03.1070U
I03.1080U
I03.1090U
I03.1100U
I03.1110U
I03.1120U
I03.1130U
I03.1140U
I03.1150U
I03.1160U
I03.1170U
I03.1180U
I03.1190U
I03.1200U
I03.1230U
I03.1250U
I03.1280U
I03.1300U
I03.1350U
I03.1380U
I03.1400U
I03.1450U
I03.1480U
I03.1500U
I03.1550U
I03.1580U
I03.1600U




Серия E03

E03.0990U
E03.1000U
E03.1010U
E03.1020U
E03.1030U
E03.1040U
E03.1050U
E03.1060U
E03.1070U
E03.1080U
E03.1090U
E03.1100U
E03.1110U
E03.1120U
E03.1130U
E03.1140U
E03.1150U
E03.1160U
E03.1170U
E03.1180U
E03.1190U
E03.1200U
E03.1230U
E03.1250U
E03.1280U
E03.1300U
E03.1350U
E03.1380U
E03.1400U
E03.1450U
E03.1480U
E03.1500U
E03.1550U
E03.1580U
E03.1600U



UNIVERSAL

Solid carbide drills 3xD



Ø d1	Ø d2	l2	l1	Max. depth of drilling
16,50	18	73	123	51
16,80	18	73	123	51
17,00	18	73	123	51
17,50	18	73	123	51
17,80	18	73	123	51
18,00	18	73	123	51
18,50	20	79	131	55
19,00	20	79	131	55
19,50	20	79	131	55
19,80	20	79	131	55
20,00	20	79	131	55

Series I03

I03.1650U
I03.1680U
I03.1700U
I03.1750U
I03.1780U
I03.1800U
I03.1850U
I03.1900U
I03.1950U
I03.1980U
I03.2000U

Universal

TIALN

Series E03


E03.1650U
E03.1680U
E03.1700U
E03.1750U
E03.1780U
E03.1800U
E03.1850U
E03.1900U
E03.1950U
E03.1980U
E03.2000U

Universal

TIALN

UNIVERSAL

Solid carbide drills 5xD



Ø d1	Ø d2	l2	l1	Max. depth of drilling
0,50	3	10	50	
0,60	3	10	50	
0,70	3	10	50	
0,80	3	10	50	
0,90	3	10	50	
1,00	3	10	55	6,5
1,10	3	12	55	9,5
1,20	3	12	55	9,5
1,30	3	12	55	9,5
1,40	3	12	55	9,5
1,50	3	12	55	9,5
1,60	3	16	55	13,0
1,70	3	16	55	13,0
1,80	3	16	55	13,0
1,90	3	16	55	13,0
2,00	3	16	57	13,0
2,10	3	21	57	16,0
2,20	3	21	57	16,0
2,30	3	21	57	16,0
2,40	3	21	57	16,0
2,50	3	21	57	16,0
2,60	3	21	57	18,5
2,70	3	21	57	18,5
2,75	3	21	57	18,5
2,80	3	21	57	18,5
2,90	3	21	57	18,5
3,00	6	28	66	23,0
3,10	6	28	66	23,0
3,20	6	28	66	23,0
3,30	6	28	66	23,0
3,40	6	28	66	23,0
3,50	6	28	66	23,0
3,60	6	28	66	23,0
3,65	6	28	66	23,0
3,70	6	28	66	23,0

Series I05

I05.0100U
I05.0110U
I05.0120U
I05.0130U
I05.0140U
I05.0150U
I05.0160U
I05.0170U
I05.0180U
I05.0190U
I05.0200U
I05.0210U
I05.0220U
I05.0230U
I05.0240U
I05.0250U
I05.0260U
I05.0270U
I05.0275U
I05.0280U
I05.0290U
I05.0300U
I05.0310U
I05.0320U
I05.0330U
I05.0340U
I05.0350U
I05.0360U
I05.0365U
I05.0370U




Series E05

E05.0050U
E05.0060U
E05.0070U
E05.0080U
E05.0090U
E05.0100U
E05.0110U
E05.0120U
E05.0130U
E05.0140U
E05.0150U
E05.0160U
E05.0170U
E05.0180U
E05.0190U
E05.0200U
E05.0210U
E05.0220U
E05.0230U
E05.0240U
E05.0250U
E05.0260U
E05.0270U
E05.0280U
E05.0290U
E05.0300U
E05.0310U
E05.0320U
E05.0330U
E05.0340U
E05.0350U
E05.0360U
E05.0370U



UNIVERSAL

Solid carbide drills 5xD



Series I05

Ø d1	Ø d2	l2	l1	Max. depth of drilling
3,80	6	36	74	29,0
3,90	6	36	74	29,0
4,00	6	36	74	29,0
4,10	6	36	74	29,0
4,20	6	36	74	29,0
4,30	6	36	74	29,0
4,40	6	36	74	29,0
4,50	6	36	74	29,0
4,60	6	36	74	29,0
4,65	6	36	74	29,0
4,70	6	36	74	29,0
4,80	6	44	82	35,0
4,90	6	44	82	35,0
5,00	6	44	82	35,0
5,10	6	44	82	35,0
5,20	6	44	82	35,0
5,30	6	44	82	35,0
5,40	6	44	82	35,0
5,50	6	44	82	35,0
5,55	6	44	82	35,0
5,60	6	44	82	35,0
5,65	6	44	82	35,0
5,70	6	44	82	35,0
5,80	6	44	82	35,0
5,90	6	44	82	35,0
6,00	6	44	82	35,0
6,10	8	53	91	43,0
6,20	8	53	91	43,0
6,30	8	53	91	43,0
6,40	8	53	91	43,0
6,50	8	53	91	43,0
6,60	8	53	91	43,0
6,70	8	53	91	43,0
6,80	8	53	91	43,0
6,90	8	53	91	43,0

Series E05

I05.0380U
I05.0390U
I05.0400U
I05.0410U
I05.0420U
I05.0430U
I05.0440U
I05.0450U
I05.0460U
I05.0465U
I05.0470U
I05.0480U
I05.0490U
I05.0500U
I05.0510U
I05.0520U
I05.0530U
I05.0540U
I05.0550U
I05.0555U
I05.0560U
I05.0565U
I05.0570U
I05.0580U
I05.0590U
I05.0600U
I05.0610U
I05.0620U
I05.0630U
I05.0640U
I05.0650U
I05.0660U
I05.0670U
I05.0680U
I05.0690U

Universal

TIALN


E05.0380U
E05.0390U
E05.0400U
E05.0410U
E05.0420U
E05.0430U
E05.0440U
E05.0450U
E05.0460U
E05.0465U
E05.0470U
E05.0480U
E05.0490U
E05.0500U
E05.0510U
E05.0520U
E05.0530U
E05.0540U
E05.0550U
E05.0560U
E05.0570U
E05.0580U
E05.0590U
E05.0600U
E05.0610U
E05.0620U
E05.0630U
E05.0640U
E05.0650U
E05.0660U
E05.0670U
E05.0680U
E05.0690U

Universal

TIALN

UNIVERSAL

Solid carbide drills 5xD



Ø d1	Ø d2	l2	l1	Max. depth of drilling
7,00	8	53	91	43,0
7,10	8	53	91	43,0
7,20	8	53	91	43,0
7,30	8	53	91	43,0
7,40	8	53	91	43,0
7,50	8	53	91	43,0
7,60	8	53	91	43,0
7,65	8	53	91	43,0
7,70	8	53	91	43,0
7,80	8	53	91	43,0
7,90	8	53	91	43,0
8,00	8	53	91	43,0
8,10	10	61	103	49,0
8,20	10	61	103	49,0
8,30	10	61	103	49,0
8,40	10	61	103	49,0
8,50	10	61	103	49,0
8,60	10	61	103	49,0
8,70	10	61	103	49,0
8,80	10	61	103	49,0
8,90	10	61	103	49,0
9,00	10	61	103	49,0
9,10	10	61	103	49,0
9,20	10	61	103	49,0
9,30	10	61	103	49,0
9,40	10	61	103	49,0
9,50	10	61	103	49,0
9,55	10	61	103	49,0
9,60	10	61	103	49,0
9,70	10	61	103	49,0
9,80	10	61	103	49,0
9,90	10	61	103	49,0
10,00	10	61	103	49,0
10,10	12	71	118	56,0
10,20	12	71	118	56,0

Series I05

I05.0700U
I05.0710U
I05.0720U
I05.0730U
I05.0740U
I05.0750U
I05.0760U
I05.0765U
I05.0770U
I05.0780U
I05.0790U
I05.0800U
I05.0810U
I05.0820U
I05.0830U
I05.0840U
I05.0850U
I05.0860U
I05.0870U
I05.0880U
I05.0890U
I05.0900U
I05.0910U
I05.0920U
I05.0930U
I05.0940U
I05.0950U
I05.0955U
I05.0960U
I05.0970U
I05.0980U
I05.0990U
I05.1000U
I05.1010U
I05.1020U

Universal

TIALN

Series E05


E05.0700U
E05.0710U
E05.0720U
E05.0730U
E05.0740U
E05.0750U
E05.0760U
E05.0770U
E05.0780U
E05.0790U
E05.0800U
E05.0810U
E05.0820U
E05.0830U
E05.0840U
E05.0850U
E05.0860U
E05.0870U
E05.0880U
E05.0890U
E05.0900U
E05.0910U
E05.0920U
E05.0930U
E05.0940U
E05.0950U
E05.0960U
E05.0970U
E05.0980U
E05.0990U
E05.1000U
E05.1010U
E05.1020U

Universal

TIALN

UNIVERSAL

Solid carbide drills 5xD



Ø d1	Ø d2	l2	l1	Max. depth of drilling
10,30	12	71	118	56,0
10,40	12	71	118	56,0
10,50	12	71	118	56,0
10,60	12	71	118	56,0
10,70	12	71	118	56,0
10,80	12	71	118	56,0
10,90	12	71	118	56,0
11,00	12	71	118	56,0
11,10	12	71	118	56,0
11,20	12	71	118	56,0
11,30	12	71	118	56,0
11,40	12	71	118	56,0
11,50	12	71	118	56,0
11,55	12	71	118	56,0
11,60	12	71	118	56,0
11,70	12	71	118	56,0
11,80	12	71	118	56,0
11,90	12	71	118	56,0
12,00	12	71	118	56,0
12,20	14	77	124	60,0
12,30	14	77	124	60,0
12,50	14	77	124	60,0
12,80	14	77	124	60,0
13,00	14	77	124	60,0
13,50	14	77	124	60,0
13,80	14	77	124	60,0
14,00	14	77	124	60,0
14,50	16	83	133	63,0
14,80	16	83	133	63,0
15,00	16	83	133	63,0
15,10	16	83	133	63,0
15,50	16	83	133	63,0
15,80	16	83	133	63,0
16,00	16	83	133	63,0
16,50	18	93	143	71,0

Series I05

I05.1030U
I05.1040U
I05.1050U
I05.1060U
I05.1070U
I05.1080U
I05.1090U
I05.1100U
I05.1110U
I05.1120U
I05.1130U
I05.1140U
I05.1150U
I05.1155U
I05.1160U
I05.1170U
I05.1180U
I05.1190U
I05.1200U
I05.1220U
I05.1230U
I05.1250U
I05.1280U
I05.1300U
I05.1350U
I05.1380U
I05.1400U
I05.1450U
I05.1480U
I05.1500U
I05.1510U
I05.1550U
I05.1580U
I05.1600U
I05.1650U




Series E05

E05.1030U
E05.1040U
E05.1050U
E05.1060U
E05.1070U
E05.1080U
E05.1090U
E05.1100U
E05.1110U
E05.1120U
E05.1130U
E05.1140U
E05.1150U
E05.1160U
E05.1170U
E05.1180U
E05.1190U
E05.1200U
E05.1220U
E05.1230U
E05.1250U
E05.1280U
E05.1300U
E05.1350U
E05.1380U
E05.1400U
E05.1450U
E05.1480U
E05.1500U
E05.1550U
E05.1580U
E05.1600U
E05.1650U



UNIVERSAL

Solid carbide drills 5xD



Ø d1	Ø d2	l2	l1	Max. depth of drilling
16,80	18	93	143	71,0
17,00	18	93	143	71,0
17,50	18	93	143	71,0
17,80	18	93	143	71,0
18,00	18	93	143	71,0
18,50	20	101	153	77,0
19,00	20	101	153	77,0
19,50	20	101	153	77,0
20,00	20	101	153	77,0

Series I05

I05.1680U
I05.1700U
I05.1750U
I05.1780U
I05.1800U
I05.1850U
I05.1900U
I05.1950U
I05.2000U

Universal

HA

wGH

TIALN

Series E05

E05.1680U
E05.1700U
E05.1750U
E05.1780U
E05.1800U
E05.1850U
E05.1900U
E05.1950U
E05.2000U

Universal

HA


w/o GH

TIALN

UNIVERSAL

Series
4I05

Solid carbide drills 5xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
3,00	6	28	66	23	4I05.0300U
3,10	6	28	66	23	4I05.0310U
3,20	6	28	66	23	4I05.0320U
3,30	6	28	66	23	4I05.0330U
3,40	6	28	66	23	4I05.0340U
3,50	6	28	66	23	4I05.0350U
3,60	6	28	66	23	4I05.0360U
3,70	6	28	66	23	4I05.0370U
3,80	6	36	74	29	4I05.0380U
3,90	6	36	74	29	4I05.0390U
4,00	6	36	74	29	4I05.0400U
4,10	6	36	74	29	4I05.0410U
4,20	6	36	74	29	4I05.0420U
4,30	6	36	74	29	4I05.0430U
4,40	6	36	74	29	4I05.0440U
4,50	6	36	74	29	4I05.0450U
4,60	6	36	74	29	4I05.0460U
4,70	6	36	74	29	4I05.0470U
4,80	6	44	82	35	4I05.0480U
4,90	6	44	82	35	4I05.0490U
5,00	6	44	82	35	4I05.0500U
5,10	6	44	82	35	4I05.0510U
5,20	6	44	82	35	4I05.0520U
5,30	6	44	82	35	4I05.0530U
5,40	6	44	82	35	4I05.0540U
5,50	6	44	82	35	4I05.0550U
5,60	6	44	82	35	4I05.0560U
5,70	6	44	82	35	4I05.0570U
5,80	6	44	82	35	4I05.0580U
5,90	6	44	82	35	4I05.0590U
6,00	6	44	82	35	4I05.0600U
6,10	8	53	91	43	4I05.0610U
6,20	8	53	91	43	4I05.0620U
6,30	8	53	91	43	4I05.0630U
6,40	8	53	91	43	4I05.0640U

Universal

140°


HA

TIALN

UNIVERSAL

Series
4105

Solid carbide drills 5xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
6,50	8	53	91	43	4105.0650U
6,60	8	53	91	43	4105.0660U
6,70	8	53	91	43	4105.0670U
6,80	8	53	91	43	4105.0680U
6,90	8	53	91	43	4105.0690U
7,00	8	53	91	43	4105.0700U
7,10	8	53	91	43	4105.0710U
7,20	8	53	91	43	4105.0720U
7,30	8	53	91	43	4105.0730U
7,40	8	53	91	43	4105.0740U
7,50	8	53	91	43	4105.0750U
7,60	8	53	91	43	4105.0760U
7,70	8	53	91	43	4105.0770U
7,80	8	53	91	43	4105.0780U
7,90	8	53	91	43	4105.0790U
8,00	8	53	91	43	4105.0800U
8,10	10	61	103	49	4105.0810U
8,20	10	61	103	49	4105.0820U
8,30	10	61	103	49	4105.0830U
8,40	10	61	103	49	4105.0840U
8,50	10	61	103	49	4105.0850U
8,60	10	61	103	49	4105.0860U
8,70	10	61	103	49	4105.0870U
8,80	10	61	103	49	4105.0880U
8,90	10	61	103	49	4105.0890U
9,00	10	61	103	49	4105.0900U
9,10	10	61	103	49	4105.0910U
9,20	10	61	103	49	4105.0920U
9,30	10	61	103	49	4105.0930U
9,40	10	61	103	49	4105.0940U
9,50	10	61	103	49	4105.0950U
9,60	10	61	103	49	4105.0960U
9,70	10	61	103	49	4105.0970U
9,80	10	61	103	49	4105.0980U
9,90	10	61	103	49	4105.0990U

Universal

140°


HA

TIALN

UNIVERSAL

Series
4105

Solid carbide drills 5xD,
4 margins



Ø d1	Ø d2	l2	l1	Max depth of drilling	
10,00	10,00	61	103	49	4105.1000U
10,10	12,00	71	118	56	4105.1010U
10,20	12,00	71	118	56	4105.1020U
10,30	12,00	71	118	56	4105.1030U
10,40	12,00	71	118	56	4105.1040U
10,50	12,00	71	118	56	4105.1050U
10,60	12,00	71	118	56	4105.1060U
10,70	12,00	71	118	56	4105.1070U
10,80	12,00	71	118	56	4105.1080U
10,90	12,00	71	118	56	4105.1090U
11,00	12,00	71	118	56	4105.1100U
11,10	12,00	71	118	56	4105.1110U
11,20	12,00	71	118	56	4105.1120U
11,30	12,00	71	118	56	4105.1130U
11,40	12,00	71	118	56	4105.1140U
11,50	12,00	71	118	56	4105.1150U
11,60	12,00	71	118	56	4105.1160U
11,70	12,00	71	118	56	4105.1170U
11,80	12,00	71	118	56	4105.1180U
11,90	12,00	71	118	56	4105.1190U
12,00	12,00	71	118	56	4105.1200U
12,20	14,00	77	124	60	4105.1220U
12,30	14,00	77	124	60	4105.1230U
12,50	14,00	77	124	60	4105.1250U
12,80	14,00	77	124	60	4105.1280U
13,00	14,00	77	124	60	4105.1300U
13,50	14,00	77	124	60	4105.1350U
13,80	14,00	77	124	60	4105.1380U
14,00	14,00	77	124	60	4105.1400U
14,50	16,00	83	133	63	4105.1450U
14,80	16,00	83	133	63	4105.1480U
15,00	16,00	83	133	63	4105.1500U
15,50	16,00	83	133	63	4105.1550U
15,80	16,00	83	133	63	4105.1580U
16,00	16,00	83	133	63	4105.1600U

Universal

140°

HA


WCH

TIALN

UNIVERSAL

Series
4105

Solid carbide drills 5xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
16,50	18,00	93	143	71	4105.1650U
16,80	18,00	93	143	71	4105.1680U
17,00	18,00	93	143	71	4105.1700U
17,50	18,00	93	143	71	4105.1750U
17,80	18,00	93	143	71	4105.1780U
18,00	18,00	93	143	71	4105.1800U
18,50	20,00	101	153	77	4105.1850U
19,00	20,00	101	153	77	4105.1900U
19,50	20,00	101	153	77	4105.1950U
20,00	20,00	101	153	77	4105.2000U

Universal

140°

HA

wGH

TIALN

UNIVERSAL

Series
4I08

Solid carbide drills 8xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
1,0	3	11	55	9,0	4I08.0100U
1,1	3	17	55	13,5	4I08.0110U
1,2	3	17	55	13,5	4I08.0120U
1,3	3	17	55	13,5	4I08.0130U
1,4	3	17	55	13,5	4I08.0140U
1,5	3	22	65	17,5	4I08.0150U
1,6	3	22	65	17,5	4I08.0160U
1,7	3	22	65	17,5	4I08.0170U
1,8	3	22	65	17,5	4I08.0180U
1,9	3	22	65	17,5	4I08.0190U
2,0	3	28	74	22,5	4I08.0200U
2,1	3	28	74	22,5	4I08.0210U
2,2	3	28	74	22,5	4I08.0220U
2,3	3	28	74	22,5	4I08.0230U
2,4	3	28	74	22,5	4I08.0240U
2,5	3	32	81	22,5	4I08.0250U
2,6	3	32	81	22,5	4I08.0260U
2,7	3	32	81	22,5	4I08.0270U
2,8	3	32	81	22,5	4I08.0280U
2,9	3	32	81	22,5	4I08.0290U
3,0	6	34	72	27,0	4I08.0300U
3,1	6	34	72	27,0	4I08.0310U
3,2	6	34	72	27,0	4I08.0320U
3,3	6	34	72	27,0	4I08.0330U
3,4	6	34	72	27,0	4I08.0340U
3,5	6	34	72	27,0	4I08.0350U
3,6	6	34	72	27,0	4I08.0360U
3,7	6	34	72	27,0	4I08.0370U
3,8	6	43	81	35,0	4I08.0380U
3,9	6	43	81	35,0	4I08.0390U
4,0	6	43	81	35,0	4I08.0400U
4,1	6	43	81	35,0	4I08.0410U
4,2	6	43	81	35,0	4I08.0420U
4,3	6	43	81	35,0	4I08.0430U
4,4	6	43	81	35,0	4I08.0440U
4,5	6	43	81	35,0	4I08.0450U
4,6	6	43	81	35,0	4I08.0460U
4,7	6	57	95	35,0	4I08.0470U
4,8	6	57	95	45,0	4I08.0480U
4,9	6	57	95	45,0	4I08.0490U

Universal

140°

HA

wGH

TIALN

UNIVERSAL

Series
4108

Solid carbide drills 8xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
5,0	6	57	95	45,0	4108.0500U
5,1	6	57	95	45,0	4108.0510U
5,2	6	57	95	45,0	4108.0520U
5,3	6	57	95	45,0	4108.0530U
5,4	6	57	95	45,0	4108.0540U
5,5	6	57	95	45,0	4108.0550U
5,6	6	57	95	45,0	4108.0560U
5,7	6	57	95	45,0	4108.0570U
5,8	6	57	95	45,0	4108.0580U
5,9	6	57	95	45,0	4108.0590U
6,0	6	57	95	45,0	4108.0600U
6,1	8	76	114	52,0	4108.0610U
6,2	8	76	114	52,0	4108.0620U
6,3	8	76	114	52,0	4108.0630U
6,4	8	76	114	52,0	4108.0640U
6,5	8	76	114	52,0	4108.0650U
6,6	8	76	114	52,0	4108.0660U
6,7	8	76	114	52,0	4108.0670U
6,8	8	76	114	52,0	4108.0680U
6,9	8	76	114	52,0	4108.0690U
7,0	8	76	114	60,0	4108.0700U
7,1	8	76	114	60,0	4108.0710U
7,2	8	76	114	60,0	4108.0720U
7,3	8	76	114	60,0	4108.0730U
7,4	8	76	114	60,0	4108.0740U
7,5	8	76	114	60,0	4108.0750U
7,6	8	76	114	60,0	4108.0760U
7,7	8	76	114	60,0	4108.0770U
7,8	8	76	114	60,0	4108.0780U
7,9	8	76	114	60,0	4108.0790U
8,0	8	76	114	60,0	4108.0800U
8,1	10	95	142	68,0	4108.0810U
8,2	10	95	142	68,0	4108.0820U
8,3	10	95	142	68,0	4108.0830U
8,4	10	95	142	68,0	4108.0840U
8,5	10	95	142	68,0	4108.0850U
8,6	10	95	142	68,0	4108.0860U
8,7	10	95	142	68,0	4108.0870U
8,8	10	95	142	68,0	4108.0880U
8,9	10	95	142	68,0	4108.0890U

Universal

140°

HA

wGH

TIALN

UNIVERSAL

Series
4108

Solid carbide drills 8xD,
4 margins



Ø d1	Ø d2	l2	l1		
9,0	10	95	142	68,0	4108.0900U
9,1	10	95	142	76,0	4108.0910U
9,2	10	95	142	76,0	4108.0920U
9,3	10	95	142	76,0	4108.0930U
9,4	10	95	142	76,0	4108.0940U
9,5	10	95	142	76,0	4108.0950U
9,6	10	95	142	76,0	4108.0960U
9,7	10	95	142	76,0	4108.0970U
9,8	10	95	142	76,0	4108.0980U
9,9	10	95	142	76,0	4108.0990U
10,0	10	95	142	76,0	4108.1000U
10,1	12	114	162	90,0	4108.1010U
10,2	12	114	162	90,0	4108.1020U
10,3	12	114	162	90,0	4108.1030U
10,4	12	114	162	90,0	4108.1040U
10,5	12	114	162	90,0	4108.1050U
10,6	12	114	162	90,0	4108.1060U
10,7	12	114	162	90,0	4108.1070U
10,8	12	114	162	90,0	4108.1080U
10,9	12	114	162	90,0	4108.1090U
11,0	12	114	162	90,0	4108.1100U
11,1	12	114	162	90,0	4108.1110U
11,2	12	114	162	90,0	4108.1120U
11,3	12	114	162	90,0	4108.1130U
11,4	12	114	162	90,0	4108.1140U
11,5	12	114	162	90,0	4108.1150U
11,6	12	114	162	90,0	4108.1160U
11,7	12	114	162	90,0	4108.1170U
11,8	12	114	162	90,0	4108.1180U
11,9	12	114	162	90,0	4108.1190U
12,0	12	114	162	90,0	4108.1200U
12,5	14	133	178	106,0	4108.1250U
12,8	14	133	178	106,0	4108.1280U
13,0	14	133	178	106,0	4108.1300U
13,5	14	133	178	106,0	4108.1350U
14,0	14	133	178	106,0	4108.1400U
14,5	16	152	203	122,0	4108.1450U
15,0	16	152	203	122,0	4108.1500U
15,5	16	152	203	122,0	4108.1550U
16,0	16	152	203	122,0	4108.1600U

Universal

140°

HA

wGH

TIALN

UNIVERSAL

Series
4I12

Solid carbide drills 12xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
1,0	3	15	55	12,0	4I12.0100U
1,1	3	23	55	18,5	4I12.0110U
1,2	3	23	55	18,5	4I12.0120U
1,3	3	23	55	18,5	4I12.0130U
1,4	3	23	55	18,5	4I12.0140U
1,5	3	23	65	18,5	4I12.0150U
1,6	3	30	65	24,0	4I12.0160U
1,7	3	30	65	24,0	4I12.0170U
1,8	3	30	65	24,0	4I12.0180U
1,9	3	30	65	24,0	4I12.0190U
2,0	3	30	74	24,0	4I12.0200U
2,1	3	38	74	30,5	4I12.0210U
2,2	3	38	74	30,5	4I12.0220U
2,3	3	38	74	30,5	4I12.0230U
2,4	3	38	74	30,5	4I12.0240U
2,5	3	38	81	30,5	4I12.0250U
2,6	3	44	81	30,5	4I12.0260U
2,7	3	44	81	35,0	4I12.0270U
2,8	3	44	81	35,0	4I12.0280U
2,9	3	44	81	35,0	4I12.0290U
3,0	6	54	92	48,0	4I12.0300U
3,3	6	54	92	48,0	4I12.0330U
3,4	6	54	92	48,0	4I12.0340U
3,5	6	54	92	48,0	4I12.0350U
3,6	6	54	92	48,0	4I12.0360U
3,7	6	54	92	48,0	4I12.0370U
3,8	6	64	102	58,0	4I12.0380U
3,9	6	64	102	58,0	4I12.0390U
4,0	6	64	102	58,0	4I12.0400U
4,1	6	64	102	58,0	4I12.0410U
4,2	6	64	102	58,0	4I12.0420U
4,3	6	64	102	58,0	4I12.0430U
4,4	6	64	102	58,0	4I12.0440U
4,5	6	64	102	58,0	4I12.0450U
4,6	6	64	102	58,0	4I12.0460U
4,7	6	64	102	58,0	4I12.0470U
4,8	6	78	116	70,0	4I12.0480U
4,9	6	78	116	70,0	4I12.0490U
5,0	6	78	116	70,0	4I12.0500U

Universal

140°

HA

wGH

TIALN

UNIVERSAL

Series
4I12

Solid carbide drills 12xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
5,1	6	78	118	70,0	4I12.0510U
5,2	6	78	118	70,0	4I12.0520U
5,3	6	78	118	70,0	4I12.0530U
5,4	6	78	118	70,0	4I12.0540U
5,5	6	78	118	70,0	4I12.0550U
5,6	6	78	118	70,0	4I12.0560U
5,7	6	78	118	70,0	4I12.0570U
5,8	6	78	118	70,0	4I12.0580U
5,9	6	78	118	70,0	4I12.0590U
6,0	6	78	118	70,0	4I12.0600U
6,1	8	78	146	94,0	4I12.0610U
6,2	8	78	146	94,0	4I12.0620U
6,3	8	78	146	94,0	4I12.0630U
6,4	8	78	146	94,0	4I12.0640U
6,5	8	78	146	94,0	4I12.0650U
6,6	8	78	146	94,0	4I12.0660U
6,7	8	78	146	94,0	4I12.0670U
6,8	8	78	146	94,0	4I12.0680U
6,9	8	78	146	94,0	4I12.0690U
7,0	8	78	146	94,0	4I12.0700U
7,1	8	78	146	94,0	4I12.0710U
7,2	8	78	146	94,0	4I12.0720U
7,3	8	78	146	94,0	4I12.0730U
7,4	8	78	146	94,0	4I12.0740U
7,5	8	78	146	94,0	4I12.0750U
7,6	8	78	146	94,0	4I12.0760U
7,7	8	78	146	94,0	4I12.0770U
7,8	8	78	146	94,0	4I12.0780U
7,9	8	78	146	94,0	4I12.0790U
8,0	8	78	146	94,0	4I12.0800U
8,1	10	120	162	110,0	4I12.0810U
8,2	10	120	162	110,0	4I12.0820U
8,3	10	120	162	110,0	4I12.0830U
8,4	10	120	162	110,0	4I12.0840U
8,5	10	120	162	110,0	4I12.0850U
8,6	10	120	162	110,0	4I12.0860U
8,7	10	120	162	110,0	4I12.0870U
8,8	10	120	162	110,0	4I12.0880U
8,9	10	120	162	110,0	4I12.0890U
9,0	10	120	162	110,0	4I12.0900U

Universal

140°

HA

wG

TIALN

UNIVERSAL

Series
4I12

Solid carbide drills 12xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
9,1	10	120	162	110,0	4I12.0910U
9,2	10	120	162	110,0	4I12.0920U
9,3	10	120	162	110,0	4I12.0930U
9,4	10	120	162	110,0	4I12.0940U
9,5	10	120	162	110,0	4I12.0950U
9,6	10	120	162	110,0	4I12.0960U
9,7	10	120	162	110,0	4I12.0970U
9,8	10	120	162	110,0	4I12.0980U
9,9	10	120	162	110,0	4I12.0990U
10,0	10	120	162	110,0	4I12.1000U
10,1	12	156	204	142,0	4I12.1010U
10,2	12	156	204	142,0	4I12.1020U
10,3	12	156	204	142,0	4I12.1030U
10,4	12	156	204	142,0	4I12.1040U
10,5	12	156	204	142,0	4I12.1050U
10,6	12	156	204	142,0	4I12.1060U
10,7	12	156	204	142,0	4I12.1070U
10,8	12	156	204	142,0	4I12.1080U
10,9	12	156	204	142,0	4I12.1090U
11,0	12	156	204	142,0	4I12.1100U
11,1	12	156	204	142,0	4I12.1110U
11,2	12	156	204	142,0	4I12.1120U
11,3	12	156	204	142,0	4I12.1130U
11,4	12	156	204	142,0	4I12.1140U
11,5	12	156	204	142,0	4I12.1150U
11,6	12	156	204	142,0	4I12.1160U
11,7	12	156	204	142,0	4I12.1170U
11,8	12	156	204	142,0	4I12.1180U
11,9	12	156	204	142,0	4I12.1190U
12,0	12	156	204	142,0	4I12.1200U
12,5	14	182	230	166,0	4I12.1250U
12,8	14	182	230	166,0	4I12.1280U
13,0	14	182	230	166,0	4I12.1300U
13,5	14	182	230	166,0	4I12.1350U
13,8	14	182	230	166,0	4I12.1380U
14,0	14	182	230	166,0	4I12.1400U
14,5	16	208	260	192,0	4I12.1450U
14,8	16	208	260	192,0	4I12.1480U
15,0	16	208	260	192,0	4I12.1500U

Universal

140°

HA

wGH

TIALN

UNIVERSAL

Series
4I12

Solid carbide drills 12xD,
4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
15,5	16	208	260	192,0	4I12.1550U
15,8	16	208	260	192,0	4I12.1580U
16,0	16	208	260	192,0	4I12.1600U
16,5	18	234	285	216,0	4I12.1650U
16,8	18	234	285	216,0	4I12.1680U
17,0	18	234	285	216,0	4I12.1700U
17,5	18	234	285	216,0	4I12.1750U
17,8	18	234	285	216,0	4I12.1780U
18,0	18	234	285	216,0	4I12.1800U
18,5	20	258	310	238,0	4I12.1850U
18,8	20	258	310	238,0	4I12.1880U
19,0	20	258	310	238,0	4I12.1900U
19,5	20	258	310	238,0	4I12.1950U
19,8	20	258	310	238,0	4I12.1980U
20,0	20	258	310	238,0	4I12.2000U

Universal

140°

HA

wG1

TIALN

UNIVERSAL

Series 4I15 Solid carbide drills 15xD, 4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
1,00	3,0	20	60	15	4I15.0100U
1,10	3,0	22	60	17	4I15.0110U
1,20	3,0	24	60	18	4I15.0120U
1,30	3,0	25	60	21	4I15.0130U
1,40	3,0	27	60	21	4I15.0140U
1,50	3,0	27	60	23	4I15.0150U
1,60	3,0	32	65	24	4I15.0160U
1,70	3,0	32	65	26	4I15.0170U
1,80	3,0	35	65	27	4I15.0180U
1,90	3,0	35	65	29	4I15.0190U
2,00	3,0	35	65	30	4I15.0200U
2,10	3,0	40	75	32	4I15.0210U
2,20	3,0	40	75	33	4I15.0220U
2,30	3,0	40	75	35	4I15.0230U
2,40	3,0	45	75	36	4I15.0240U
2,50	3,0	45	75	38	4I15.0250U
2,60	3,0	48	80	39	4I15.0260U
2,70	3,0	48	80	41	4I15.0270U
2,80	3,0	50	80	42	4I15.0280U
2,90	3,0	50	80	44	4I15.0290U
3,00	6,0	60	100	45	4I15.0300U
3,10	6,0	60	100	47	4I15.0310U
3,20	6,0	60	100	48	4I15.0320U
3,30	6,0	60	100	50	4I15.0330U
3,40	6,0	60	100	51	4I15.0340U
3,50	6,0	60	100	53	4I15.0350U
3,60	6,0	68	115	54	4I15.0360U
3,70	6,0	68	115	56	4I15.0370U
3,80	6,0	68	115	57	4I15.0380U
3,90	6,0	68	115	59	4I15.0390U
4,00	6,0	68	115	60	4I15.0400U
4,10	6,0	78	115	62	4I15.0410U
4,20	6,0	78	115	63	4I15.0420U
4,30	6,0	78	115	65	4I15.0430U
4,40	6,0	78	115	66	4I15.0440U
4,50	6,0	78	115	68	4I15.0450U
4,60	6,0	84	130	69	4I15.0460U
4,70	6,0	84	130	71	4I15.0470U
4,80	6,0	84	130	72	4I15.0480U
4,90	6,0	84	130	74	4I15.0490U

Universal

140°

HA

TIALN

UNIVERSAL

Series 4115 Solid carbide drills 15xD, 4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
5,0	6	92	130	75	4115.0500U
5,1	6	92	130	77	4115.0510U
5,2	6	92	130	78	4115.0520U
5,3	6	92	130	80	4115.0530U
5,4	6	92	130	81	4115.0540U
5,5	6	100	145	83	4115.0550U
5,6	6	100	145	84	4115.0560U
5,7	6	100	145	86	4115.0570U
5,8	6	100	145	87	4115.0580U
5,9	6	100	145	90	4115.0590U
6,0	6	100	145	90	4115.0600U
6,1	8	108	145	92	4115.0610U
6,2	8	108	145	93	4115.0620U
6,3	8	108	145	96	4115.0630U
6,4	8	108	145	96	4115.0640U
6,5	8	130	170	97	4115.0650U
6,6	8	130	170	99	4115.0660U
6,7	8	130	170	101	4115.0670U
6,8	8	130	170	102	4115.0680U
6,9	8	130	170	102	4115.0690U
7,0	8	130	170	105	4115.0700U
7,5	8	130	170	115	4115.0750U
7,8	8	130	170	117	4115.0780U
8,0	8	130	170	120	4115.0800U
8,5	10	163	208	128	4115.0850U
8,8	10	163	208	132	4115.0880U
9,0	10	163	208	135	4115.0900U
9,5	10	163	208	143	4115.0950U
9,8	10	163	208	147	4115.0980U
10,0	10	163	245	150	4115.1000U
10,2	12	195	245	153	4115.1020U
10,5	12	195	245	158	4115.1050U
10,8	12	195	245	162	4115.1080U
11,0	12	195	245	165	4115.1100U
11,2	12	195	245	168	4115.1120U
11,5	12	195	245	173	4115.1150U
11,8	12	195	245	177	4115.1180U
12,0	12	195	245	180	4115.1200U
12,5	14	230	280	188	4115.1250U
13,0	14	230	280	195	4115.1300U

Universal

140°

HA

wGH

TIALN

UNIVERSAL

Series 4I15 Solid carbide drills 15xD, 4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
13,8	14	230	280	207	4I15.1380U
14,0	14	230	280	210	4I15.1400U
14,8	16	260	260	222	4I15.1480U
15,0	16	260	260	225	4I15.1500U
15,8	16	260	260	237	4I15.1580U
16,0	16	260	260	240	4I15.1600U

Universal

140°

HA

wGH

TIALN

UNIVERSAL

Series 4120 Solid carbide drills 20xD, 4 margins



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
2,0	4	50	92	50	4120.0200U
2,2	4	50	92	50	4120.0220U
2,3	4	50	92	50	4120.0230U
2,4	4	70	112	70	4120.0240U
2,5	4	70	112	70	4120.0250U
2,7	4	70	112	70	4120.0270U
2,8	4	70	112	70	4120.0280U
3,0	6	80	120	80	4120.0300U
3,2	6	80	120	80	4120.0320U
3,3	6	80	120	80	4120.0330U
3,5	6	80	120	80	4120.0350U
3,8	6	90	130	90	4120.0380U
4,0	6	90	130	90	4120.0400U
4,2	6	110	160	110	4120.0420U
4,5	6	110	160	110	4120.0450U
4,8	6	120	160	120	4120.0480U
5,0	6	120	160	120	4120.0500U
5,5	6	140	185	140	4120.0550U
5,8	6	140	185	140	4120.0580U
6,0	6	140	185	140	4120.0600U
6,5	8	155	210	155	4120.0650U
6,8	8	160	210	160	4120.0680U
7,0	8	160	210	160	4120.0700U
7,5	8	180	230	180	4120.0750U
7,8	8	180	230	180	4120.0780U
8,0	8	180	230	180	4120.0800U
8,5	10	195	260	195	4120.0850U
8,8	10	230	290	230	4120.0880U
9,0	10	230	290	230	4120.0900U
9,8	10	230	290	230	4120.0980U
10,0	10	230	290	230	4120.1000U
10,2	12	270	315	270	4120.1020U
10,8	12	270	315	270	4120.1080U
11,8	12	270	315	270	4120.1180U
12,0	12	270	315	270	4120.1200U

Universal

140°

HA

wCh

TIALN

UNIVERSAL

Series
PI05

Solid carbide drills 15xD, pilot



Ø d1	Ø d2	l2	l1	Max. depth of drilling	
2,02	3	16	57	16	PI05.0202U
2,22	3	21	57	21	PI05.0222U
2,32	3	21	57	21	PI05.0232U
2,42	3	21	57	21	PI05.0242U
2,52	3	21	57	21	PI05.0252U
2,72	3	21	57	21	PI05.0272U
2,82	3	21	57	21	PI05.0282U
3,02	6	28	66	28	PI05.0302U
3,22	6	28	66	28	PI05.0322U
3,32	6	28	66	28	PI05.0332U
3,52	6	28	66	28	PI05.0352U
3,82	6	36	74	36	PI05.0382U
4,02	6	36	74	36	PI05.0402U
4,22	6	36	74	36	PI05.0422U
4,52	6	36	74	36	PI05.0452U
4,82	6	44	82	44	PI05.0482U
5,02	6	44	82	44	PI05.0502U
5,52	6	44	82	44	PI05.0552U
5,82	6	44	82	44	PI05.0582U
6,02	6	44	82	44	PI05.0602U
6,52	8	53	91	53	PI05.0652U
6,82	8	53	91	53	PI05.0682U
7,02	8	53	91	53	PI05.0702U
7,52	8	53	91	53	PI05.0752U
7,82	8	53	91	53	PI05.0782U
8,02	8	53	91	53	PI05.0802U
8,52	10	61	103	61	PI05.0852U
8,82	10	61	103	61	PI05.0882U
9,02	10	61	103	61	PI05.0902U
9,82	10	61	103	61	PI05.0982U
10,02	10	61	103	61	PI05.1002U
10,22	12	71	118	71	PI05.1022U
10,82	12	71	118	71	PI05.1082U
11,82	12	71	118	71	PI05.1182U
12,02	12	71	118	71	PI05.1202U

Universal


140°

HA

TIALN

UNIVERSAL

Series E03S
Solid carbide step drills



Ø d1	Ø d2	l2	l1	l3	
2,5/6,0	6	28	66	8,8	E03S.0250.0600U
3,3/6,0	6	28	66	11,4	E03S.0330.0600U
4,2/6,0	6	28	66	13,6	E03S.0420.0600U
5,0/8,0	8	41	79	16,5	E03S.0500.0800U
6,8/10,0	10	47	89	21,0	E03S.0680.1000U
8,5/12,0	12	55	102	25,5	E03S.0850.1200U
10,2/14,0	14	60	107	30	E03S.1020.1400U

Universal

140°

HA

w/o CH

TIALN

30°

Material	Vc	ø1-2	ø 2-3	ø 3-5	ø 5-8	ø 8-12	ø 12 - 16	ø 16 - 20
unalloyed steels, steel castings	60-100	0,03-0,05	0,05-0,08	0,1-0,18	0,16-0,24	0,2-0,3	0,2-0,33	0,25-0,4
alloyed steels	50-80	0,02-0,04	0,05-0,08	0,08-0,15	0,10-0,18	0,12-0,22	0,15-0,28	0,2-0,35
	40-80	0,02-0,04	0,05-0,08	0,08-0,15	0,10-0,18	0,12-0,22	0,15-0,28	0,2-0,35
inox	30-50	0,01-0,03	0,03-0,06	0,06-0,10	0,08-0,15	0,12-0,20	0,1-0,2	0,16-0,28
corrosion- and acid-proof steels (CrNi-alloyed)	25-35	0,01-0,03	0,03-0,06	0,05-0,10	0,08-0,15	0,12-0,20	0,1-0,2	0,16-0,28
grey cast iron, alloyed grey cast iron	50-130			0,15-0,30	0,12-0,30	0,2-0,4	0,25-0,40	0,4-0,5
	70-90			0,15-0,30	0,12-0,30	0,2-0,4	0,25-0,40	0,4-0,5
spheroidal graphite	70-90		0,05-0,10	0,1-0,2	0,1-0,2	0,2-0,4	0,35-0,45	0,4-0,6
	60-80			0,08-0,12	0,1-0,18	0,16-0,28	0,22-0,33	0,3-0,5
Alu forgeable alby	50-350	0,04-0,07	0,01-0,15	0,15-0,25	0,2-0,3	0,25-0,40	0,35-0,5	0,4-0,6
cast alu alloy < 10% Si	100-250		0,05-0,12	0,15-0,25	0,2-0,3	0,25-0,40	0,35-0,5	0,4-0,6
cast alu alloy > 10% Si	100-200	0,6-0,8	0,6-0,10	0,12-0,20	0,18-0,22	0,20-0,28	0,26-0,3	0,25-0,32
copper, bronze, brass, short-chipping	60-200	0,05-0,08	0,08-0,15	0,07-0,15	0,10-0,20	0,20-0,30	0,25-0,40	0,35-0,50
titanium alloys	20-40	0,01-0,03	0,03-0,06	0,02-0,06	0,05-0,08	0,08-0,14	0,10-0,16	0,10-0,20
hardened materials	25-35	0,01-0,02	0,02-0,03	0,06-0,08	0,07-0,09	0,1-0,13	0,12-0,15	
	20-25	0,01-0,02	0,02-0,03	0,03-0,05	0,04-0,06	0,08-0,1	0,12-0,15	
	15-20	0,01-0,02	0,02-0,03	0,03-0,05	0,04-0,06	0,08-0,1	0,1-0,12	
	10-15	0,01-0,02	0,02-0,03	0,03-0,05	0,04-0,06	0,08-0,1	0,1-0,12	

Drill depth	Factor of correction
1xd	1,3
3xd	1,0
5xd	0,8
8xd	0,7
12xd	0,6
15xd	0,5

